


KTZ35.5-53 380-415V
Technical specification
3~ 50 Hz

Pump

Series	KTZ
Pump name	KTZ35.5-53 380-415V
Standard	

Motor data

Motor	SM2-2-5.5KTZ 400DYT N
Rated voltage	380 V
Frequency	50 Hz
Motor phases	3~
Number of poles	2
Rated power P2	5.5 kW
Rated current	11.6 A
rpm	2945 1/min
Rated torque	17.8 Nm
Start*	Direct starting

Degree of protection	IP 68
Insulation class	F
Protection device	Circle thermal protector
Type of oil	Turbine oil VG32
Oil amount	1.1 l

Hydraulic

Free passage	
Impeller type	Semi-open impeller
Max. hydraulic efficiency	50.1 %
Discharge	80 mm
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. liquid temperature	40 °C
Max. density treated liquid	1030 kg/m³
pH treated liquid	5-9
Max. start per hour (equally distributed)	10
Wet/dry use	WET
Operating mode	S1

Construction materials

Motor enclosure	Gray Iron Casting 150
Shaft	420J2 Stainless Steel
Pump Casing	Gray Iron Casting 200
Impeller	High chromium casting
Suction Cover	Ductile Iron Casting 500
Suction plate	N/A
Painting	-
Screws	304 Stainless Steel
Gaskets	NBR

Construction features

Power cable1	4C*3.5mm2
Power cable2	N/A
Sheath	2PNCT.F
Control cable	N/A
Sheath	N/A
Cable length*	8 m
Mechanical seals	H-25T
Weight**	74 kg

* Please inquire about cable extensions
 ** cable's weight not included

Monitoring features


Monitoring option	
leaking sensor -	
monitoring equipment -	

KTZ35.5-53 380-415V

Pump performance curves

3 ~ 50 Hz

Discharge	Head	Capacity	Rated power	Voltage	Current	rpm
80 mm			5.5 kW	380 V	11.6 A	2945 1/min




A210954_N5_P-C_KTZ35_5-53I

Created on: 2026-06-23

All data shown are not binding. Tsurumi reserves the right to change data and dimensions without notice.

SECTIONAL DRAWING		No.		No.	A-21109-45
TYPE	Submersible Dewatering Pump		MODEL	KTZ35.5 -53	





REQ. SPECIFICATION

No.	DESCRIPTION	Q'TY	MATERIAL / NOTE	No.	DESCRIPTION	Q'TY	MATERIAL / NOTE
1	Cabtyre Cable	1	Chloroprene Sheath	50	Motor Bracket	1	Gray Iron Casting 200
6	Stuffing Box	1	Gray Iron Casting 200	52A	Upper Bearing	1	6305ZZC3
20	Pump Casing	1	Gray Iron Casting 200	52B	Lower Bearing	1	6308ZZC3
21	Impeller	1	Chromium Iron Casting	53	Motor Protector	1	
22	Suction Cover	1	Ductile Iron Casting 500	54	Shaft	1	420J2 Stainless Steel
23	Strainer Stand	1	Steel Sheet	55	Rotor	1	
25	Mechanical Seal	1	H-25T	56	Stator	1	
26	Oil Seal	1	TC40588	60	Bearing Housing	1	Gray Iron Casting 150
30	Oil Lifter	1	Plastic	64	Motor Frame	1	Gray Iron Casting 150
32	Hose Coupling	1	Aluminium Die Casting 12	68	Handle	1	Carbon Steel Pipe & Structure Steel
35	Oil Plug	1	304 Stainless Steel				
36	Lubricant		Turbine Oil(ISO VG32)				

DIMENSION DRAWING		No.		No.	A-21105-35
TYPE	Submersible Dewatering Pump		MODEL	KTZ35.5 -53	

Approximate Weight(※)
74kg

※excluding cable



C.W.L.:Continuous running Water Level

TSURUMI MFG. CO., LTD.

unit:mm

Created on: 2026-06-23